

ETOWAH CHEMICAL SALES & SERVICE

DIVISION OF H. P. W. SPECIALTIES, INC.
2618 Forrest Avenue
Gadsden, Alabama 35904-0416
800-848-8541



N. F. P. A.
4 = Extreme
3 = High
2 = Moderate
1 = Slight
0 = Insignificant

HEALTH	3
FIRE	0
REACTIVITY	0
PERSONAL PROTECTION	C

Material Safety Data Sheet

24 Hour Emergency Telephone Number: (800) 535-5053

SECTION I - IDENTIFICATION

Product Name	MIGHTY STRIP FLOOR STRIPPER	Date last Revised	August 2009
Chemical Family	ALKALINE CLEANER	Item Number	ETC-1371
Proper D.O.T. Shipping Name	CORROSIVE LIQUID, n.o.s.		
D.O.T. Hazard Classification	8, UN 1760, PG III (contains Sodium hydroxide)		

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

% By Weight	Material	PEL	T. L. V.	C. A. S. No.
15-20	2-BUTOXYETHANOL*	25 ppm	25 ppm	111-76-2
<3	SODIUM HYDROXIDE	2mg/m3	2mg/m3	1310-58-3
<5	MONOETHANOLAMINE	3 ppm	3 ppm	141-43-5
	ITEMS MARKED* ARE SARA TITLE III SEC 313 REPORTABLE			
	Balance non-hazardous ingredients			

SECTION III - PHYSICAL DATA

Boiling Point	212 F	pH (Conc.)	ABOVE 13.5
Solubility In Water	COMPLETE	pH (Use Dilution)	1% 12.0
% Volatility By Weight	<90	Evaporation Rate	H ₂ O=1 >1
Specific Gravity	1.035	Physical Form	LIQUID
Appearance And Odor	CLEAR, COLORLESS; ETHER ODOR		

SECTION IV - FIRE AND EXPLOSION DATA INGREDIENTS/IDENTITY

Flash Point	NONE
Extinguishing Media	N/A
Flammable Limits	N/A
Special Fire Fighting Procedures	WEAR SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE DEMAND MODE.
Unusual Fire and Explosion Hazards	CONCENTRATED PRODUCT CAN REACT WITH ALUMINUM, ZINC, MAGNESIUM AND COPPER TO FORM HYDROGEN GAS WHICH CAN FORM EXPLOSIVE MIXTURES WITH AIR.

SECTION V - REACTIVITY DATA

Stability	STABLE
Conditions to Avoid	EXTREME HEAT
Incompatibility	ACIDS, NON-FERROUS METALS, SKIN
Hazardous Decomposition Products	NONE
Hazardous Polymerization	WILL NOT OCCUR

SECTION VI - HEALTH HAZARD	
Routes(s) of Entry	Inhalation? Yes Skin? YES Ingestion? NO
Health Hazards (Acute and Chronic)	EYES: CAN CAUSE SEVERE IRRITATION AND BURNS. SKIN: BURNS AND IRRITATION. INGESTION: CAUSES BURNS OF GASTRO-INTENSIONAL TRACT. INHALATION: EXCESSIVE INHALATION CAN CAUSE NASAL AND RESPIRATORY IRRITATION.
Carcinogenicity	NTP NO IARC NO OSHA Regulated? NO
Emergency Aid and First Aid Procedures	EYES: FLUSH WITH WATER FOR 15 MINUTES. IF EYE DAMAGE OCCURS, CONSULT AN OPHTHALMOLOGIST. SKIN: FLUSH WITH WATER FOR 15 MINUTES. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT ADMINISTER OXYGEN. INGESTION: DO NOT INDUCE VOMITING DILUTE WITH WATER OR MILK. CALL A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON
SECTION VII - SPILL OR LEAK PROCEDURES	
Spill Response	CLEAN-UP WORKERS MUST USE PROTECTIVE CLOTHING TO PREVENT BODY CONTACT. PICK UP WITH WET MOP, WET VAC OR ABSORBENT MATERIAL. RINSE FLOOR WITH CLEAR WATER AND ALLOW FLOOR TO DRY BEFORE ALLOWING TRAFFIC.
Waste Disposal Method	DILUTE WITH WATER AND ADJUST pH WITH DILUTE ACID TO A pH BELOW 9.0, THEN FLUSH TO A SANITARY SEWER. DRY MATERIAL MUST BE SENT TO A HAZARDOUS WASTE LANDFILL FOLLOWING LOCAL STATE AND FEDERAL REGULATIONS.
SECTION VIII - SPECIAL PROTECTION INFORMATION	
Eye Protection	WEAR FACE SHIELDS AND SPLASH GOGGLES.
Skin Protection	WEAR RUBBER GLOVES.
Ventilation	NORMAL ROOM VENTILATION.
Respiratory Protection	NONE REQUIRED IN NORMAL CONDITIONS. WHEN EXCESSIVE MISTS ARE GENERATED ABOVE TLV'S USE A RESPIRATOR.
Other Protection	RUBBER BOOTS AND RUBBER APRONS ARE ALSO NEEDED.
SECTION IX - SPECIAL PRECAUTIONS	
Precautions in Handling and Storage	KEEP OUT OF REACH OF CHILDREN. STORE AT ROOM TEMPERATURE . RINSE CONTAINER BEFORE DISCARDING. STORE AWAY FROM ACIDS.
Other Precautions	DO NOT USE UNDILUTED (AT LEAST 100 TO 1) ON ALUMINUM OR LATEX PAINTED SURFACES.
PREPARED BY: David Brunton, Chemist	
Disclaimer of Liability. As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Conforms to OSHA 174 , Sep. 1985.	