

**ETOWAH CHEMICAL
SALES & SERVICE**
P.O. BOX 4416
GADSDEN, AL 35904-0416
(800) 848-8541



N. F. P. A.
4 = Extreme
3 = High
2 = Moderate
1 = Slight
0 = Insignificant

HEALTH	2
FIRE	0
REACTIVITY	0
PERSONAL PROTECTION	C

Material Safety Data Sheet

24 Hour Emergency Telephone Number: (800) 535-5053

SECTION I - IDENTIFICATION

Product Name	SUPER 60 CONCRETE REMOVER	Date Prepared	APRIL 2009
Chemical Family	ACID CLEANER	Item Number	ETC-1079
Proper D.O.T. Shipping Name	CORROSIVE LIQUID, n.o.s.		
D.O.T. Hazard Classification	8, UN-1760, PG III (contains Phosphoric Acid)		

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

% By Weight	Material	PEL	T. L. V.	C. A. S. No.
40	PHOSPHORIC ACID	1 mg/m ³	3 mg/m ³	7664-38-2
	SARA TITLE III REPORTING REQUIREMENTS SECTION 313 REQUIRED IF OVER 20,000 POUNDS IS USED PER YEAR. SECTION 311, 312 REQUIRED			
	Balance non-hazardous ingredients			

SECTION III - PHYSICAL DATA

Boiling Point	215 DEG F	pH (Conc.)	BELOW 1.5
Solubility In Water	COMPLETE	pH (Use Dilution)	1% 1.6
% Volatility By Weight	<64	Evaporation Rate	WATER=1 > 1
Specific Gravity	1.210	Physical Form	LIQUID
Appearance And Odor	CLEAR, COLORLESS, SLIGHT ACID ODOR		

SECTION IV - FIRE AND EXPLOSION DATA INGREDIENTS/IDENTITY INFORMATION

Flash Point	NONE
Extinguishing Media	REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICAL
Flammable Limits	N/A
Special Fire Fighting Procedures	WEAR SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATE IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES
Unusual Fire and Explosion Hazards	ACIDS REACT WITH MOST METALS TO RELEASE HYDROGEN GAS, WHICH MAY FORM AN EXPLOSIVE MIXTURE WITH AIR

SECTION V - REACTIVITY DATA

Stability	STABLE
Conditions to Avoid	OXIDIZERS
Incompatibility	AVOID STRONG ALKALIES, OXIDIZERS, CHLORINE BLEACH
Hazardous Decomposition Products	MAY FORM TOXIC ACID VAPORS
Hazardous Polymerization	WILL NOT OCCUR

SECTION VI - HEALTH HAZARD	
Routes(s) of Entry	Inhalation? NO Skin? NO Ingestion? NO
Health Hazards (Acute and Chronic)	EYES: WILL CAUSE BURNS AND DAMAGE VERY RAPIDLY. SKIN: WILL CAUSE IRRITATION. INHALATION: MISTS ARE IRRITATING TO MUCOUS MEMBRANE. INGESTION: RESULTS IN DAMAGE TO MUCOUS MEMBRANES.
Carcinogenicity	NTP? NO IARC Monographs? NO OSHA Regulated? NO
Emergency Aid and First Aid Procedures	EYES: FLUSH WITH WATER FOR 20 MINUTES WHILE CALLING FOR IMMEDIATE MEDICAL ATTENTION. SKIN: FLUSH WITH RUNNING WATER. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. INGESTION: DO NOT INDUCE VOMITING. DILUTE WITH WATER. GIVE MILK OF MAGNESIA. SEEK MEDICAL ATTENTION
SECTION VII - SPILL OR LEAK PROCEDURES	
Spill Response	COVER THE CONTAMINATED SURFACE WITH SODIUM BICARBONATE (BAKING SODA), OR SLAKED LIME AND ADD WATER TO FORM A SLURRY. SCOOP UP SLURRY AND WASH DOWN SITE WITH SODIUM BICARBONATE SOLUTION.
Waste Disposal Method	DILUTE WITH WATER, ADJUST ph WITH SODIUM BICARBONATE TO A ph ABOVE 6.0 AND BELOW 9.0, THEN FLUSH TO SANITARY SEWER FOLLOWING LOCAL, STATE AND FEDERAL REGULATIONS
SECTION VIII - SPECIAL PROTECTION INFORMATION	
Eye Protection	WEAR SAFETY GLASSES CHEMICAL SPLASH GOGGLES.
Skin Protection	WEAR NEOPRENE GLOVES.
Ventilation	NORMAL ROOM VENTILATION.
Respiratory Protection	If TLV of any component is exceeded, use a NIOSH approved full face respirator.
Other Protection	NEOPRENE APRON AND BOOTS
SECTION IX - SPECIAL PRECAUTIONS	
Precautions in Handling and Storage	KEEP OUT OF REACH OF CHILDREN. KEEP AWAY FROM OXIDIZING AGENTS AND ALKALIES. RINSE CONTAINERS BEFORE DISPOSAL. REPORTABLE UNDER RCRA.
Other Precautions	SAFETY SHOWER, EYE BATH AND WASHING FACILITIES SHOULD BE AVAILABLE.
PREPARED BY: David Brunton, Chemist	
<p>Disclaimer of Liability.</p> <p>As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Conforms to OSHA 174 , Sep. 1985.</p>	