



SC-103

ASPHALT RELEASE AGENT

(APPROVED BY THE STATE OF ALABAMA)

SC-103 IS AN ECONOMICAL AND EFFICIENT, **WATER BASED** ASPHALT RELEASE. WHEN MIXED AT THE RECOMMENDED CONCENTRATIONS, **SC-103** PRODUCES A FOAM THAT **IS NOT HARMFUL** TO HOT ASPHALT MIXES.

SC-103 HAS HEAT RESISTANT ADDITIVES TO ENSURE RELEASE AT HIGH TEMPERATURES, PREVENTING BUILD-UP IN TRUCK BEDS. **SC-103** COMPLIES WITH **D.O.T. NON-PETROLEUM HYDROCARBON** REQUIREMENTS. THIS PRODUCT **WILL NOT** HARM ALUMINUM OR STEEL TRUCK BEDS WHEN USED AT RECOMMENDED DILUTIONS.

SPECIFICATIONS

Physical appearance.....	Clear, amber liquid
Odor.....	None
Specific gravity.....	1.040
pH.....	8.5-9.5 (at room temp)
Viscosity.....	100 cps (at room temp)
Biodegradable	yes
Freeze point.....	30 degrees F.
Phosphorous as % p.....	None
Flash point.....	None

DIRECTIONS:

SC-103 IS USED AT A DILUTION OF 1:20 WITH WATER FOR TYPICAL RELEASE APPLICATIONS. FOR DIFFICULT TO RELEASE MIXES (RUBBERIZED OR POLYMER ENHANCED) USE AT A 1:15 DILUTION. BEST RESULTS ARE ACHIEVED WHEN THE MIX IS FOAMED ONTO THE TRUCK BED. **SC-103** CAN BE DILUTED AND DISPENSED WITH MANUAL OR POWER/PUMPING **HUDSON TYPE SPRAYERS**. WASTE DISCHARGES SHOULD BE MADE IN ACCORDANCE WITH PERMIT REQUIREMENTS.

FIRST AID:

If **EYE** contact occurs, flush with large quantities of water for at least 15 minutes. If **INGESTED**, give 2 glasses of milk or water, **DO NOT** induce vomiting. **Get medical attention immediately.** **SKIN**, flush with water for at least 5 minutes.

MANUFACTURED BY:

ETOWAH CHEMICAL SALES & SERVICE

PO BOX 4416 **** Gadsden, Alabama 35904,
1-800-848-8541