



SC-15

EXTRA HEAVY DUTY DEGREASER

SC-15 is used in steam cleaners and high pressure machines for cleaning the heaviest type of grease and oils from equipment. It is generally used where paint damage is of no concern, such as on motor blocks, earth moving machines, trucks, driveways, and greasy floors. **SC-15** helps keep down scale buildup because of the water softening properties. **SC-15** is a highly concentrated formulation that is **phosphate-free** and **biodegradable**.

SPECIFICATIONS

Physical Appearance.....	Red liquid
Odor.....	Slight surfactant odor
Specific Gravity.....	1.100
pH.....	13.5 (conc.) 12.3 (use dilution)
Viscosity.....	1 centistoke at 20 C
Biodegradable	yes
Freeze Point.....	-5.5 C
Phosphorous as % P.....	None
Flash Point.....	None

DIRECTIONS:

Calculate dilution to use 1/2 TO 1oz. of product per gallon of water, i.e. 1 gallon for each 100 gallons of water. For extremely tough cleaning, use 2 to 3 gallons of product to each 100 gallons of water. Adjust metering valve until small amount of suds can be seen at the spray nozzle head.

DANGER:

Causes burns and irritation. Harmful if swallowed. **Keep out of reach of children.** Store at room temperature. Rinse container before discarding. Store away from acids. Contains sodium hydroxide and biodegradable detergents. Avoid contact of undiluted products with skin or eyes. Avoid continued inhalation of mists in spraying or other applications. Wear goggles and rubber gloves when using in power washing equipment.

FIRST AID:

If **eye** contact occurs, flush thoroughly with water for 15 min. Get immediate medical help. For **skin**, flush with water. If **ingested**, give water or milk. Do not induce vomiting. Get medical attention immediately.

ETOWAH CHEMICAL SALES & SERVICE

PO BOX 4416 ***** Gadsden, Alabama 35904

800-848-8541