



SC-EB-24

OIL WATER SEPARATOR CHEMICAL

SC-EB-24 is designed specifically for use in cleaning operations having oil/water separators to clear up the waste. It is useful in a wide range of cleaning operations such as pressure washing, truck washing, etc., where a moderately alkaline cleaner is required.

SPECIFICATIONS:

Physical Appearance.....	Clear, brown liquid
Odor.....	None
Specific Gravity.....	1.060
pH.....	11.3 (1% use dilution)
Viscosity.....	1 centistoke
Biodegradable	yes
Freeze point.....	-5 C
Phosphorous % P.....	100 ppm
Flash point.....	None

DIRECTIONS:

Typical dilutions vary. Normal use will be 1 part **SC-EB-24** to 50 parts water. Once the emulsified effluent goes to the still water tank, the oil and grease will break the emulsion in 30 minutes or less. This will then allow the oil and grease to be skimmed for disposal as hazardous waste.

FOR INDUSTRIAL/COMMERCIAL USE ONLY.

CAUTION:

Keep containers tightly closed when not in use. Do not take internally. Prolonged contact with skin causes irritation. Contact with eyes cause severe irritation. See the msds for further information

FIRST AID

If eye contact occurs, flush with water for 15 minutes. If irritation persists, get medical attention. If skin contact occurs flush with water. Get medical attention if irritation persists.

ETOWAH CHEMICAL SALES & SERVICE

PO BOX 4416 ***** Gadsden, Alabama 35904
1-800-848-8541