



# STORM

## VEHICLE & TRUCK WASH

\*\*\*\*\*

**STORM** is designed specifically for use in cleaning operations having oil/water separators to break oil/water emulsion in the waste stream, so they may be discharged of quickly. It is useful in a wide range of cleaning operations, such as pressure washing, truck washing, etc., where a moderately alkaline cleaner is required. It has quick demulsifying degreasers, **biodegradable surfactants** and alkalinity builders to dissolve grease and grime.

### SPECIFICATIONS

Physical appearance.....	Clear, yellow liquid
Odor.....	None
Specific gravity.....	1.080
pH.....	11.5 (at 1% solution)
Viscosity.....	1 centistoke
<b>Biodegradable</b> .....	yes
Freeze point.....	-5 degrees F.
Phosphorous as % p.....	None
Flash point.....	None

### DIRECTIONS:

Typical dilutions vary. Normal use will be 1 part **STORM** to 40-50 parts water at spray tip. Once the emulsified effluent goes to the still water holding tank, the oil and grease will break the emulsion in 30 minutes or less. This will then allow the oil and grease to be collected and disposed of as recommended by local and state authorities.

### FIRST AID:

If **EYE** contact occurs, flush with large quantities of water for at least 15 minutes. If **INGESTED**, give 2 glasses of milk or water, **DO NOT** induce vomiting. **Get medical attention immediately.** **SKIN**, flush with water for at least 5 minutes.

MANUFACTURED BY:

**ETOWAH CHEMICAL SALES & SERVICE**  
**P.O. BOX 4416 : Gadsden, Alabama 35904**  
**(800) 848-8541**