



TOOL KOOL

SYNTHETIC CUTTING FLUID
and CORROSION INHIBITOR

Tool Kool is a synthetic all purpose cutting coolant excellent for cutting, grinding or drilling metals. Tool Kool solutions are very low foaming making them easier to use than most oil based and semi-synthetic coolants. Its high amount of corrosion inhibitors prevents flash rusting of machined parts and cutting tools, it works great as a short term corrosion inhibitor for ferrous metals. Tool Kool does not contain oils or phosphates making it's solutions easier to dispose.

SPECIFICATIONS

Physical appearance.....	Clear, green liquid
Odor.....	Sassafras odor
Specific gravity.....	1.075
pH.....	9.0-10.0 (at room temp)
Viscosity.....	1 cps (at room temp)
Freeze point.....	-11
Phosphorous as % p.....	None
Flash point.....	None

DIRECTIONS:

Use Tool Kool at dilutions of 8 to 16 ounces per gallon of water in the cutting fluid tank.

HANDLING AND STORAGE:

Store below 120 F in order to preserve product stability.

FIRST AID:

If eye contact occurs, flush with large quantities of water for at least 15 minutes. If ingested, induce vomiting immediately by sticking finger down throat. Get medical attention immediately.

ETOWAH CHEMICAL SALES AND SERVICE

PO BOX 4416 **** Gadsden, Alabama 35904
800-848-8541