

LIQUID SPRAY WAX (RTU)

LIQUID SPRAY WAX is a highly refined organic surfactant system which bonds to paint surface to improve gloss, enhance sheeting of water, discourage spotting and improve drying time. **Biodegradable**. See dilution ratio below under directions.

TYPICAL PROPERTIES:

Physical appearance..... Clear, light amber liquid
odor..... Lemon
Specific gravity.....1.0 @ 20 degrees c (68 degrees f)
ph..... 7.0 @ 20 degrees c (68 degrees f)
Viscosity..... 2000 cps @ 20 degrees c (68 degrees f)
Freeze point..... 30 degrees f
Phosphorous as % p..... none
Biodegradable.....yes
flash point..... none

DIRECTIONS: **LIQUID SPRAY WAX** should be metered at a dilution rate of 4 to 6 ounces of wax per car or for duration of rinse cycle. For use through high pressure washers, meter this solution on to vehicle at a rate of 1 part wax to 25 parts water, hot or cold.

CAUTION: Do not use, spill or store near open flame, sparks or heat. Avoid prolonged breathing of vapor. Use with adequate ventilation. Avoid prolonged or repeated skin contact. When using, wear splash proof goggles and rubber gloves. Contains 2-butoxy-ethanol, **Biodegradable** detergents. Avoid contact of undiluted products with skin or eyes.

FIRST AID: If eye contact occurs, flush thoroughly with water for 15 min. get immediate medical help. If ingested, give water or milk. Do not induce vomiting. If affected by vapors, move to fresh air. Get medical attention immediately.

MANUFACTURED BY:

ETOWAH CHEMICAL SALES & SERVICE
PO BOX 4416 ----- Gadsden, AL 35904
800-848-8541